

Just Resin Epoxy Pigment Paste

High Quality Epoxy Pigment Paste, made from Finely Ground Powders. Designed to tint Just Resin epoxy resin systems effortlessly. Just Resin Pigment Pastes will quickly disperse into your medium and are highly concentrated, therefore only a small amount is required to reach desired tint.

Characteristics

- Formulated for use with Epoxy Resin
- Unique effects
- Strong opacity
- Australian Made
- Blendable with other JR Pigments

Application

Allow the pigment paste to settle prior to opening the jar and stir well before use. We recommend starting at a 1% pigment loading and incorporate into your mixed epoxy resin. Slowly increase the loading until your desired tone is achieved, ensuring not to exceed a ratio of 10% pigment to epoxy resin.

Storage

Pigment pastes have a shelf life of 12 months and are best stored in a warm (20c to 25c), dry cupboard for longevity. Jar to be stored top side up, with lids tightly closed.

Should the pigment consistency alter due to cold temperatures (and high pigment loading which gives such intense vivid colours), condition the pigment by placing the pigment in a plastic bag, and then in a bowl of hot water for approximately 20mins, and give a good stir, ensuring to not allow the water to enter the jar of. This process can be repeated if necessary. If you wish, you may also add a few millilitres of Part A (resin only) to the jar of pigment once its fluid, which will extend it out.

Cautions

- Keep out of reach of Children.
- Do not ingest.
- In the instance of tinting an epoxy resin system other than Just Resin, we recommend you conduct a small test to ensure compatibility.
- Refer to Safety Data Sheet before use.

DISCLAIMER : All technical data, recommendations and service are accurate to the best of our knowledge. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Just Resin assumes no responsibility for the results obtained or damage incurred from use by the buyer in whole or in part, since the method of application and its use is beyond our control. We reserve the right to alter product constants within the scope of technical progress or new developments. It is the responsibility of the user to ensure a proper assessment has been carried out. No representation or warranties, either expressed or implied, or merchantability, fitness for purpose or any other nature are made here under with Respect to the product to which this information refers.